

CX SERIES

DEDICATED HORIZONTAL COPPER COIL



Unit shown with service panels removed. Representative image only. Some models may vary in appearance.

STANDARD FEATURES

- Rifled copper tubing, enhanced aluminum fins.
- Immersion tested at 500 psi, followed by nitrogen pressurization and factory sealing to ensure optimal system integrity and long-term reliability.
- Refrigerant lines exit top of coil. Schrader valve on suction line for pressure assurance testing. **Refrigerant and plumbing connections:**
 - **All Drain Pan Connections:** 3/4" NPT
- Heavy duty polypropylene drain pans.
- Inlet and outlet opening dimensions are identical (without end caps).
- Three-piece service door on top for easy service access.
- Fully insulated cabinets with faced insulation.
- ETL and AHRI listed for R22, R410A, R454B, and R32 refrigerants [A2L Refrigerants certified with Refrigerant Detection System (RDS)].
- A2L refrigerants require a Refrigerant Detection System (RDS) for compliance.
- AHRI certifiable with all brands of A/C and heat pump systems.

WARRANTY

- Ten-year limited warranty with registration.

CUSTOMIZATION OPTIONS*

UNIVERSAL A2L REFRIGERANT TECHNOLOGY FOR R32 & R454B SYSTEMS

Aspen coils and air handlers are engineered with Universal A2L Refrigerant Technology, allowing field configurability for either R32 or R454B refrigerants. Each unit ships with a factory-installed A2L metering device that can be easily swapped at installation, and includes the option for a factory- or field-installed universal Refrigerant Detection System (RDS) compatible with both refrigerants.

OTHER POPULAR CUSTOM OPTIONS:

- Refrigerant Detection System (RDS) kit factory-installed.
- Factory or field-installed TXV available.

DEDICATED HORIZONTAL COIL CX SERIES

CX-SS-C-007-B




In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2025 Aspen Manufacturing. All Rights Reserved

Customer Service: info@aspenmfg.com Warranty Team: warranty@aspenmfg.com Phone: 281.441.6500 Toll Free: 800.423.9007 Fax: 281.441.6510



WWW.ASPENMFG.COM

FIGURE 1



DIMENSIONAL DATA (In.) - FIGURE 1

COIL MODEL	NOM. CAPACITY BTU	DIMENSIONS						SHIPPING INFO.			
		CABINET				OPENING		WEIGHT (LBS)			SKID QTY
		WIDTH	DEPTH	MAX. HEIGHT	TRANSITION HEIGHT AVAILABLE OPTIONS	WIDTH	HEIGHT	# OF ROWS			
		A"	B"	C"	T"	D"	E"	2	3	4	
CX24A*	24,000	21	22	14-1/2	14 / 14-1/2	20	13-1/2	-	35	39	16
CX24B*		21	22	15	14 / 14-1/2 / 15	20	14	-	37	42	16
CX24E*		21	27	17-1/2	14 / 14-1/2 / 17-1/2	20	16-1/2	43	50	57	16
CX30A*	30,000	21	22	15	14 / 14-1/2 / 15	20	14	-	37	42	16
CX30E*		21	27	17-1/2	14 / 14-1/2 / 17-1/2	20	16-1/2	-	50	57	16
CX36A*	36,000	21	22	15	14 / 14-1/2 / 15	20	14	-	37	42	16
CX36B*		21	27	17-1/2	14 / 14-1/2 / 17-1/2	20	16-1/2	-	47	53	16
CX36C*		21	22	17-1/2	14 / 14-1/2 / 17-1/2	20	16-1/2	-	41	47	16
CX36D*		21	32	21	14 / 14-1/2 / 17-1/2 / 21	20	20	-	66	75	6
CX36E*		21	27	21	14 / 14-1/2 / 17-1/2 / 21	20	20	-	56	65	12
CX36F*		21	27	17-1/2	14 / 14-1/2 / 17-1/2	20	16-1/2	-	47	53	16
CX42C*	42,000	21	27	21	14 / 14-1/2 / 17-1/2 / 21	20	20	-	58	67	12
CX42D*		21	32	21	14 / 14-1/2 / 17-1/2 / 21	20	20	-	65	74	6
CX48A*	48,000	21	27	17-1/2	14 / 14-1/2 / 17-1/2	20	16-1/2	-	49	56	16
CX48B*		21	27	21	14 / 14-1/2 / 17-1/2 / 21	20	20	-	56	64	12
CX48C*		21	27	21	14 / 14-1/2 / 17-1/2 / 21	20	20	-	56	65	12
CX48D*		21	32	21	14 / 14-1/2 / 17-1/2 / 21	20	20	-	66	75	6
CX60A*	60,000	21	27	21	14 / 14-1/2 / 17-1/2 / 21	20	20	-	58	67	6
CX60B*		21	32	21	14 / 14-1/2 / 17-1/2 / 21	20	20	-	66	75	6
CX60C*		21	32	24-1/2	21 / 24 / 24-1/2	20	23-1/2	-	77	90	6
CX60D*		21	32	25	21 / 24 / 24-1/2 / 25	20	24	-	79	91	6
CX60E*		21	32	25	21 / 24 / 24-1/2 / 25	20	24	-	82	95	6
CX60F*		21	32	24-1/2	21 / 24 / 24-1/2	20	23-1/2	-	69	79	6

DRAIN PAN TEMPERATURE TABLE

DRAIN PAN TYPE	TEMPERATURE LIMITS
Plastic - Standard	290°

CX-SS-C-007-B

HELPFUL LINKS



VIEW PRODUCT ONLINE

For full warranty terms and conditions, please refer to the Warranty Information section on Aspen's official website.



ASK YOUR LOCAL SALES REP OR SCAN TO LEARN MORE

Aspen's A2L Refrigerant Technology for R32 and R454B Systems.

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2025 Aspen Manufacturing. All Rights Reserved

Customer Service: info@aspenmfg.com Warranty Team: warranty@aspenmfg.com Phone: 281.441.6500 Toll Free: 800.423.9007 Fax: 281.441.6510