



Representative image only. Some models may vary in appearance. Due to continuous product improvement, specifications are subject to change without notice.

### Product Features and Specifications

- Rifled copper tubing, enhanced aluminum fins.
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed.
- Left or right-hand refrigerant and plumbing connections.
- Liquid line - 3/8" ODS, suction line - 3/4" ODS on 1-1/2 3 ton and 7/8" ODS on 3-1/2 - 5 ton.
- Externally mounted flowrate body with Schrader valve for hiss-testing
- Heavy duty plastic drain pans on most models.
- Upflow without field modification. Downflow applications require plate kit, sold separately.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454A, and R-32 when proper metering device is used.
- Ten-year limited warranty. For complete warranty details, please visit [www.AspenMfg.com](http://www.AspenMfg.com)

### Customization

- Factory or field-installed TXV available.
- Powder-painted metal or stainless pans.
- Schrader mounted on suction manifold, external to cabinet.

### Downflow Kit Part Numbers

- **METAL DRAIN PANS** 16" DWNFLWM-16 & 18" DWNFLWM-18
- **PLASTIC DRAIN PANS** DWNFLWP



COIL MODEL	NOMINAL CAPACITY (BTUs)	FLOW RATOR SIZE R 410-A	DIMENSIONS						SHIPPING INFORMATION			
			PAN WIDTHS (W)"				PAN DEPTH (D)"	BARE SLAB HEIGHT (H)"	SHIPPING WEIGHT (LBS)			SKID QTY
			13	16	19-1/2	23			2 ROW	3 ROW	4 ROW	
CA24A*	24,000	0.055	13	16	19-1/2	N/A	19-3/8	13-1/2	17	27	35	30
CA24B*		0.055	13	16	19-1/2	N/A	19-3/8	15-1/2	20	31	41	25
CA24C*		0.055	13	16	19-1/2	N/A	19-3/8	17-1/2	23	36	47	25
CA24D*		0.055	13	16	19-1/2	N/A	19-3/8	19-1/2	25	40	53	20
CA30A*	30,000	0.059	13	16	19-1/2	N/A	19-3/8	15-1/2	20	31	41	25
CA30B*		0.059	13	16	19-1/2	N/A	19-3/8	17-1/2	23	36	47	25
CA30C*		0.059	13	16	19-1/2	N/A	19-3/8	19-1/2	25	40	53	20
CA30D*		0.059	13	16	19-1/2	N/A	19-3/8	21-1/2	28	45	58	16
CA30E*		0.059	13	16	19-1/2	N/A	19-3/8	21-1/2	30	47	60	16
CA36A*	36,000	0.068	13 for 2, 3R; 16 for 4R	16	19-1/2	N/A	19-3/8	17-1/2	23	36	47	25
CA36B*		0.068	13 for 2, 3R; 16 for 4R	16	19-1/2	N/A	19-3/8	19-1/2	25	40	53	20
CA36C*		0.068	13 for 2, 3R; 16 for 4R	16	19-1/2	N/A	19-3/8	21-1/2	28	45	58	16
CA36D*		0.068	13 for 2, 3R; 16 for 4R	16	19-1/2	N/A	19-3/8	23-1/2	31	49	64	12
CA42A*	42,000	0.074	N/A	16	19-1/2	23	19-3/8	25-1/2	25	40	53	20
CA42B*		0.074	N/A	16	19-1/2	23	19-3/8	21-1/2	28	45	58	16
CA42C*		0.074	N/A	16	19-1/2	23	19-3/8	23-1/2	31	49	64	12
CA42D*		0.074	N/A	16	19-1/2	23	19-3/8	25-1/2	34	54	70	12
CA48A*	48,000	0.080	N/A	16	19-1/2	23	19-3/8	21-1/2	28	45	58	16
CA48B*		0.080	N/A	16	19-1/2	23	19-3/8	23-1/2	31	49	64	12
CA48C*		0.080	N/A	16	19-1/2	23	19-3/8	25-1/2	34	54	70	12
CA48D*		0.080	N/A	16	19-1/2	23	19-3/8	27-1/2	37	58	76	12
CA48F*		0.080	N/A	16	19-1/2	23	19-3/8	25-1/2	36	56	72	12
CA48G*		0.080	N/A	16	19-1/2	23	19-3/8	27-1/2	39	60	78	12
CA60A*	60,000	0.089	N/A	N/A	19-1/2	23	19-3/8	25-1/2	34	54	70	12
CA60B*		0.089	N/A	N/A	19-1/2	23	19-3/8	27-1/2	37	58	76	12
CA60C*		0.089	N/A	N/A	19-1/2 (2)	23 (2)	21-3/4	24-1/2	38	60	79	12
CA60D*		0.089	N/A	N/A	19-1/2 (2)	23 (2)	21-3/4	26-1/2	41	65	86	12
CA60E*		0.089	N/A	N/A	N/A	24 (3)	21	26-1/2	46	73	95	12
CA60F*		0.089	N/A	N/A	19-1/2	23	19-3/8	25-1/2	41	62	80	12
CA60G*		0.089	N/A	N/A	N/A	24 (3)	21	26-1/2	48	75	97	12

CA Spec-2024-09-V002

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.

**DRAIN PAN TEMPERATURE TABLE**

DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°