



Product Features and Specifications

- Rifled copper tubing, enhanced aluminum fins.
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed.
- Left or right-hand refrigerant and plumbing connections.
- Liquid line - 3/4" ODS, suction line - 3/4" ODS on 1-1/2 3 ton and 7/8" ODS on 3-1/2 - 5 ton.
- Externally mounted flowrater body with Schrader valve for hiss-testing.
- Heavy duty plastic drain pans on most models, powder coated galvanized steel horizontal drain pans standard on all.
- Upflow, horizontal right, ior horizontal left without field modification. Downflow applications require plate kit, sold seperately.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454A, and R-32 when proper metering device is used.
- Ten-year limited warranty. For complete warranty details, please visit www.AspenMfg.com

Customization

- Factory or field-installed TXV available.
- Painted cabinets.
- Powder-painted metal or stainless pans.
- Schrader mounted on suction manifold, external to cabinet.

Downflow Kit Part Numbers

- **METAL DRAIN PANS** 16" DWNFLWM-16 & 18" DWNFLWM-18
- **PLASTIC DRIAN PANS** DWNFLWP

Unit shown with service panels removed. Representative drawing only. Some models may vary in appearance. Duct opening dimensions can be ascertained by subtracting 1-½ for top opening width/depth, ¾" for bottom opening.

COIL MODEL	NOMINAL CAPACITY (BTUs)	FLOW RATOR SIZE R 410-A	DIMENSIONS				SHIPPING INFORMATION			
			CABINET WIDTH (W)"		CABINET DEPTH (D)"	CABINET HEIGHT (H)"	SHIPPING WEIGHT (LBS)			SKID QTY
			MIN WIDTH	MAX WIDTH			2 ROW	3 ROW	4 ROW	
CE24A*	24,000	0.055	14	23	21-1/2	19	31	39	46	20
CE24B*		0.055	14	23	21-1/2	19	36	45	54	20
CE24C*		0.055	14	23	21-1/2	23	41	52	61	12
CE24D*		0.055	14	23	21-1/2	23	46	58	69	12
CE30A*	30,000	0.059	14	23	21-1/2	19	36	45	54	20
CE30B*		0.059	14	23	21-1/2	23	41	52	61	12
CE30C*		0.059	14	23	21-1/2	23	46	58	69	12
CE30D*		0.059	14	23	21-1/2	27	52	65	77	12
CE30E*		0.059	14	23	21-1/2	27	54	67	79	12
CE36A*	36,000	0.068	14 for 2, 3R; 17 for 4R	23	21-1/2	23	41	52	61	12
CE36B*		0.068	14 for 2, 3R; 17 for 4R	23	21-1/2	23	46	58	69	12
CE36C*		0.068	14 for 2, 3R; 17 for 4R	23	21-1/2	27	52	65	77	12
CE36D*		0.068	14 for 2, 3R; 17 for 4R	23	21-1/2	27	57	71	84	12
CE36F*		0.068	17	26-1/2	21-1/2	30	67	84	100	10
CE42A*	42,000	0.074	17	26-1/2	21-1/2	23	46	58	69	12
CE42B*		0.074	17	26-1/2	21-1/2	27	52	65	77	12
CE42C*		0.074	17	26-1/2	21-1/2	27	57	71	84	12
CE42D*		0.074	17	26-1/2	21-1/2	30	62	78	92	10

CE Spec-2024-09-V002

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.

COIL MODEL	NOMINAL CAPACITY (BTUs)	FLOW RATOR SIZE R 410-A	DIMENSIONS				SHIPPING INFORMATION			
			CABINET WIDTH (W)"		CABINET DEPTH (D)"	CABINET HEIGHT (H)"	SHIPPING WEIGHT (LBS)			SKID QTY
			MIN WIDTH	MAX WIDTH			2 ROW	3 ROW	4 ROW	
CE48A*	48,000	0.080	17	26-1/2	21-1/2	27	52	65	77	12
CE48B*		0.080	17	26-1/2	21-1/2	30	57	71	84	12
CE48C*		0.080	17	26-1/2	21-1/2	30	62	78	92	10
CE48D*		0.080	17	26-1/2	21-1/2	30	67	84	100	10
CE48F*		0.080	17	26-1/2	21-1/2	30	64	80	94	10
CE48G*		0.080	17	26-1/2	21-1/2	30	69	86	102	10
CE60A*	60,000	0.089	20-1/2	26-1/2	21-1/2	30	62	78	92	10
CE60B*		0.089	20-1/2	26-1/2	21-1/2	30	67	84	100	10
CE60C* (3)		0.089	20-1/2	26-1/2	23	30	70	88	104	10
CE60D* (3)		0.089	20-1/2	26-1/2	23	30	76	95	112	10
CE60F*		0.089	20-1/2	26-1/2	21-1/2	30	64	80	94	10

DRAIN PAN TEMPERATURE TABLE	
DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°

CE Spec-2024-09-V002

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.