



Unit shown with service panels removed. Representative image only. Some models may vary in appearance. Duct opening dimensions can be ascertained by subtracting 1-1/2" for top opening width/depth, 3/4 for bottom opening. Due to continuous product improvement, specifications are subject to change without notice.

For complete warranty details visit www.AspenMfg.com

Product Features and Specifications

- Rified copper tubing, enhanced aluminum fins.
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed.
- Left or right-hand refrigerant and plumbing connections.
- Liquid line - 3/8" ODS, suction line - 3/4 ODS on 1-1/2 3 ton and 7/8 ODS on 3-1/2 - 5 ton.
- Externally mounted flowrater body with Schrader valve for hiss-testing.
- Heavy duty plastic drain pans on most models.
- Embossed galvanized cabinets standard. Cabinets feature furnace connectors (patent pending).
- Upflow without field modification. Downflow applications require plate kit, sold separately.
- Split access doors in front for easy access.
- Fully insulated cabinets with faced insulation.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454A, and R-32 when proper metering device is used.
- Ten-year limited warranty.

Customization

- Factory or field-installed TXV available
- Painted cabinets
- Powder-painted metal or stainless pans
- Schrader mounted on suction manifold, external to cabinet
- Bikini cabinets

Downflow Kit Part Numbers

- **METAL DRAIN PANS** 16" DWNFLWM-16 & 18" DWNFLWM-18
- **PLASTIC DRIAN PANS** DWNFLWP

COIL MODEL	NOMINAL CAPACITY (BTUs)	DIMENSIONS				SHIPPING INFORMATION			
		CABINET				SHIPPING WEIGHT (LBS)			SKID QTY
		MIN WIDTH	MAX WIDTH	DEPTH	HEIGHT	2 ROW	3 ROW	4 ROW	
CC24A*	24,000	14	23	21-1/2	16	29	37	45	20
CC24B*					34	44	52		
CC24C*					20	39	50	59	
CC24D*						44	56	67	
CC30A*	30,000	14	23	21-1/2	16	34	44	52	20
CC30B*					20	39	50	59	16
CC30C*						44	56	67	
CC30D*					24	49	62	74	12
CC30E*	51	64	76						
CC36A*	36,000	2/3R - 14, 4R-17	23	21-1/2	20	39	50	59	16
CC36B*					44	56	67		
CC36C*					24	49	62	74	12
CC36D*						54	69	82	
CC36E*	20	39	50	59	16				
CC36F*	28	63	81	96	12				
CC42A*	42,000	17	26-1/2	21-1/2	20	44	56	67	16
CC42B*					24	49	62	74	12
CC42C*						54	69	82	
CC42D*					28	59	75	89	16
CC42E*					20	44	45	67	16
CC42F*					28	63	81	96	12

CC Spec-2024-11-V002

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.

COIL MODEL	NOMINAL CAPACITY (BTUs)	DIMENSIONS				SHIPPING INFORMATION			SKID QTY
		CABINET				SHIPPING WEIGHT (LBS)			
		MIN WIDTH	MAX WIDTH	DEPTH	HEIGHT	2 ROW	3 ROW	4 ROW	
CC48A*	48,000	17	26-1/2	21-1/2	24	49	62	74	12
CC48B*						54	69	82	
CC48C*					28	58	75	89	
CC48D*						63	81	96	
CC48F*						60	77	91	
CC48G*						65	83	98	
CC60A*	60,000	20-1/2	26-1/2	23	28	58	75	89	
CC60B*						63	81	96	
CC60C* (3)						66	84	100	
CC60D* (3)				71		91	108		
CC60E* (3)				79		101	120		
CC60F*				21-1/2		60	77	91	
CC60G* (4)						81	103	122	

DRAIN PAN TEMPERATURE TABLE	
DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°