



### Product Features and Specifications

- Rifled copper tubing, enhanced aluminum fins.
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed.
- Left-hand refrigerant and plumbing connections, with downturn suction line for easy installation in manufactured housing applications.
- Downflow plates and manufactured housing drain hose included.
- Liquid line - 3/8" ODS, suction line - 3/4" ODS on 1-1/2 - 3 ton and 7/8" ODS on 3-1/2 - 5 ton.
- Liquid line Schrader valve for coil pressurization-confirmation testing.
- Heavy duty polypropylene drain pans.
- Drain connection: 177L pans have single LH 3/4" FPT, 195L pans have quad drains, 3/4" FPT.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454A, and R-32 when proper metering device is used.
- Ten-year limited warranty. For complete warranty details, please visit [www.AspenMfg.com](http://www.AspenMfg.com).

Representative image only. Some models may vary in appearance. Due to continuous product improvement, specifications are subject to change without notice.

| COIL MODEL    | NOMINAL CAPACITY (BTUs) | DIMENSIONS      |            |                            | SHIPPING INFORMATION  |        |       |          |    |    |
|---------------|-------------------------|-----------------|------------|----------------------------|-----------------------|--------|-------|----------|----|----|
|               |                         | PAN             |            | COIL BARE SLAB HEIGHT (H)" | SHIPPING WEIGHT (LBS) |        |       | SKID QTY |    |    |
|               |                         | WIDTH (W)"      | DEPTH (D)" |                            | 2 ROW                 | 3 ROW  | 4 ROW |          |    |    |
| CM24A(2,3)*   | 24,000                  | 17-3/4          | 19-5/8     | 13-1/2                     | 17                    | 27     | N/A   | 30       |    |    |
| CM24B(2,3)*   |                         |                 |            | 15-1/2                     | 20                    | 31     |       | 25       |    |    |
| CM24C(2,3)*   |                         |                 |            | 17-1/2                     | 23                    | 36     |       | 20       |    |    |
| CM24D(2,3)*   |                         |                 |            | 19-1/2                     | 25                    | 40     |       | 25       |    |    |
| CM30A(2,3)*   | 30,000                  | 17-3/4          | 19-5/8     | 15-1/2                     | 20                    | 31     | N/A   | 25       |    |    |
| CM30B(2,3)*   |                         |                 |            | 17-1/2                     | 23                    | 36     |       | 20       |    |    |
| CM30C(2,3)*   |                         |                 |            | 19-1/2                     | 25                    | 40     |       | 25       |    |    |
| CM36A(2,3,4)* |                         |                 |            | 17-1/2                     | 23                    | 36     |       | 47       | 25 |    |
| CM36B(2,3,4)* | 36,000                  | N/A             | 23         | 19-1/2                     | 25                    | 40     | 53    | 20       |    |    |
| CM36C34*      |                         |                 |            | N/A                        | 25                    | N/A    | 14    |          |    |    |
| CM42A(2,3)*   | 42,000                  | 17-3/4          | 19-5/8     | 19-1/2                     | 25                    | 40     | 55    | 20       |    |    |
| CM42A4*       |                         |                 | 19-1/2     | 17-1/2                     | N/A                   | 50     | 25    |          |    |    |
| CM48A3*       | 48,000                  | 17-3/4          | 19-5/8     | 21-1/2                     | N/A                   | 45     | 60    | 16       |    |    |
| CM48A4*       |                         |                 | 19-1/2     |                            |                       |        |       |          |    |    |
| CM48B3*       |                         |                 | 19-5/8     | 23-1/2                     |                       | 49     | 63    | 12       |    |    |
| CM48B4*       |                         |                 | 19-1/2     |                            |                       |        |       |          |    |    |
| CM48C3*       |                         |                 | 19-5/8     | 25-1/2                     |                       | 54     | 68    |          |    |    |
| CM48C4*       |                         |                 | 19-1/2     |                            |                       |        |       |          |    |    |
| CM48D3*       |                         |                 | 19-5/8     | 27-1/2                     |                       | 58     | 72    |          |    |    |
| CM48D4*       |                         |                 | 19-1/2     |                            |                       |        |       |          |    |    |
| CM48E3*       |                         |                 | 19-5/8     | 19-1/2                     |                       | 40     | 55    | 20       |    |    |
| CM48E4*       |                         |                 | 19-1/2     |                            |                       |        |       |          |    |    |
| CM59A4*       | 60,000                  | 17-3/4 - 19-1/2 | 19-1/2     | 19-1/2                     | 34                    | 54     | 70    | 12       |    |    |
| CM60A3*       |                         | 19-1/2          |            |                            | 19-1/2                | 25-1/2 | 37    |          | 58 | 76 |
| CM60A4*       |                         |                 |            |                            |                       | 27-1/2 | 38    |          | 60 | 79 |
| CM60B3*       |                         |                 |            |                            |                       | 41     | 65    |          | 86 |    |
| CM60B4*       |                         |                 |            |                            |                       | 46     | 73    |          | 95 |    |

Notes: Use metal drain pan on oil furnaces or other applications where outlet temperatures may exceed 290°F +/-5°F.

**DRAIN PAN TEMPERATURE TABLE**

| DRAIN PAN TYPE      | TEMP LIMITS |
|---------------------|-------------|
| Plastic - Standard  | 290°        |
| Plastic - High Temp | 425°        |
| Metal - High Temp   | 600°        |