

NOMENCLATURE

UNIVERSAL ASPEN COIL & SERIAL NUMBER

D **A** **24** **A3** **D** **-145** **L** **-400**

①

②

③

④

⑤

⑥

⑦

⑧

⑧ **OPTION CODE**

⑦ **LOCATION OF REFRIGERANT & PLUMBING CONNECTIONS**

- L** = Left-hand
- R** = Right-hand
- T** = refrigerant out the top, plumbing out opposite sides

⑥ **WIDTH CODE** _____

EXAMPLE(S): 130 = 13", 145 = 14.5", 160 = 16", 195 = 19.5", 245 = 24.5", etc.

- **DRAIN PAN:** CA, DA, CM, & DM Series
- **FURNACE:** CC, CE, CP, CX, DC, DE, DP, & DX Series

⑤ **METERING DEVICES** _____

A2L (R32 / R454B) REFRIGERANTS

- D** = Non-Bleed A/C or H/P R32 TXV
- J** = Non-Bleed A/C or H/P R454B TXV
- K** = 20% Bleed A/C or H/P R454B TXV
- M** = R32 Piston
- N** = R454B Piston

A1 (R22 / R410A) REFRIGERANTS

- 4** = Non-Bleed A/C or H/P R410 TXV
- X** = Non-Bleed A/C or H/P R22 TXV
- B** = 20% Bleed A/C or H/P R22 TXV
- 6** = 20% Bleed A/C or H/P R410 TXV
- F** = R22 Piston
- G** = R410A Piston

④ **COIL DESCRIPTOR CODE** _____

- **LETTER:** Model Type
- **NUMBER OF ROWS:** 1-4
- **FPI:** Fins Per Inch

③ **NOMINAL TONNAGE (MBTUH)** _____

18 = 18,000 **30** = 30,000 **42** = 42,000
24 = 24,000 **36** = 36,000 **48** = 48,000

② **CONFIGURATION** _____

- A** = Uncased up/down
- C** = Cased up/down
- E** = Cased multi-position VersaCoil
- M** = Manufactured home coil
- H** = Cased dedicated horizontal slab coil
- P** = Cased dedicated horizontal with attached plenum
- X** = Cased dedicated horizontal coil

① **SERIES** _____

- C** = C Series (Copper)
- D** = D Series (Aluminum)

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. UNIVERSALCOIL-NOMEN-2025-02

